U.S.S.N.: 10/082,466

Response to Office Action

Page 4 of 25

## Amendments to the Claims

This listing of claims will replace all prior versions, and listing, of claims in the application.

## **Listing of Claims:**

1. (Currently Amended) An optical reproducing device comprising:

predetermined length mark signal measurement means for measuring respective reproduction signal characteristics respectively of a short reproducing power control mark and of a long reproducing power control mark from information data that is recorded in data recording area of an optical recording medium; and

power control means for controlling reproducing power of a light beam based on the measured reproduction signal characteristics of the short and long reproducing power control marks.

wherein the predetermined length mark signal measurement means is further configured and arranged for detecting detects a specific pattern including the short reproducing power control mark from a bit arrangement pattern of the information data in the data recording area, and measures for measuring the reproduction signal characteristic corresponding only to the short reproducing power control mark included in the specific pattern.

2. (Currently Amended) The optical reproducing device of claim 1, An optical reproducing device comprising:

predetermined length mark signal measurement means for measuring reproduction signal characteristics respectively of a short reproducing power control mark and of a long reproducing

U.S.S.N.: 10/082,466

Response to Office Action

Page 5 of 25

power control mark from information data that is recorded in a data recording area of an optical recording medium;

power control means for controlling reproducing power of a light beam based on the measured reproduction signal characteristics of the short and long reproducing power control marks; and

\_\_\_\_\_wherein the predetermined length mark signal measurement means includes:

data reproduction means for reproducing information data bits from a reproduction signal of the optical recording medium;

comparison means for comparing the a bit arrangement pattern of the information data reproduced by the data reproduction means with the a specific pattern including the short reproducing power control mark, and for detecting coincidence a coincidence of the specific pattern in the bit arrangement pattern of the information data; and

signal measurement means for measuring the reproduction signal characteristic of information data bits corresponding to the short reproducing power control mark included in the specific pattern detected by the comparison means to coincide with the bit arrangement pattern.

3. (Original) The optical reproducing device of claim 1, wherein:

the short reproducing power control mark is a mark having a length of 2T (where T is a. channel bit length), and the specific pattern is constituted by a pattern having a length arrangement of mT 2T 2T nT (where m and n are predetermined positive integers).

U.S.S.N.: 10/082,466 Response to Office Action

Page 6 of 25

4. (Original) The optical reproducing device of claim 2, wherein:

the short reproducing power control mark is a mark having a length of 2T (where T is a channel bit length), and the specific pattern is constituted by a pattern having a length arrangement of mT 2T 2T nT (where m and n are predetermined positive integers).

- 5. (Original) The optical reproducing device of claim 3, wherein m = n = 2.
- 6. (Original) The optical reproducing device of claim 4, wherein m = n = 2.
- 7. (Original) The optical reproducing device of claim 1, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.
- 8. (Original) The optical reproducing device of claim 2, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.
- 9. (Original) The optical reproducing device of claim 3, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.

U.S.S.N.: 10/082,466

Response to Office Action Page 7 of 25

10. (Original) The optical reproducing device of claim 4, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.

11. (Original) The optical reproducing device of claim 5, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.

- 12. (Original) The optical reproducing device of claim 6, further comprising reproduction condition control means for controlling a reproduction condition based on the measured reproduction signal characteristics.
  - 13. (Original) The optical reproducing device of claim 7, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

the reproduction condition control means controls the reproducing power of the light beam so that the measured amplitude ratio gets close to a target value.

U.S.S.N.: 10/082,466

Response to Office Action

Page 8 of 25

医牙髓 精工的人的

14. (Original) The optical reproducing device of claim 8, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

the reproduction condition control means controls the reproducing power of the light beam so that the measured amplitude ratio gets close to a target value.

15. (Original) The optical reproducing device of claim 9, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

1. (fill.)

the reproduction condition control means controls the reproducing power of the light and the second condition control means controls the reproducing power of the light and the second condition condition control means controls the reproducing power of the light and the second condition control means controls the reproducing power of the light and the second condition control means controls the reproducing power of the light and the second condition control means controls the reproducing power of the light and the second condition control means beam so that the measured amplitude ratio gets close to a target value.

16. (Original) The optical reproducing device of claim 10, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

the reproduction condition control means controls the reproducing power of the light beam so that the measured amplitude ratio gets close to a target value.

17. (Original) The optical reproducing device of claim 11, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

1. 11.

U.S.S.N.: 10/082,466

Response to Office Action

Page 9 of 25

the reproduction condition control means controls the reproducing power of the light beam so that the measured amplitude ratio gets close to a target value.

18. (Original) The optical reproducing device of claim 12, wherein:

the predetermined length mark signal measurement means measures a ratio between amplitude values of the short and long reproducing power control marks; and

the reproduction condition control means controls the reproducing power of the light beam so that the measured amplitude ratio gets close to a target value.

19. (New) The optical reproducing device of any of claims 1-6, wherein:

a plurality of short and long reproducing control marks are recorded in the optical recording medium;

the predetermined length mark signal measurement means measures the reproduction signal characteristics corresponding to each short reproducing mark and calculates an average value using the measured reproduction signal characteristics.

U.S.S.N.: 10/082,466

Response to Office Action

Page 10 of 25

20. (New) The optical reproducing device of any of claims 13-16, wherein:

a plurality of short and long reproducing control marks are recorded in the optical recording medium;

the predetermined length mark signal measurement means:

measures the reproduction signal characteristics corresponding to each short and long reproducing control marks,

calculates an average value for each of the short and long reproducing marks using the measured reproduction signal characteristics, and

calculates a ratio between average amplitude values of the short and long reproducing power control marks; and

the reproduction condition control means controls the reproducing power of the light beam so that the calculated amplitude ratio based on the average amplitude values gets close to a target value.